

# STUDOR® MAXI-FILTRA™

Active Carbon Filter Designed to Eliminate Bad Odours Produced by the Drainage System

## Product Information/Specification Sheet

### DESCRIPTION

The Studor Maxi-Filtra is an active carbon filter designed to eliminate bad odours produced by the drainage system. For use externally, it operates as a 2-way vent, filtering air in both directions. Particularly for use with septic tanks, the Maxi-Filtra may also be installed on open vents already existing or for new buildings where regulations insist on their inclusion within the building's drainage system.

For best results, the Studor Maxi-Filtra should be installed in conjunction with Air Admittance Valves from the Studor System.

### FEATURES

- Replaceable carbon filter cartridge.
- Prevents the release of foul air from the drainage system.
- Requires no specialist installation.
- Available in black ABS.

### INSTALLATION

- The Maxi-Filtra should be connected to the piping in accordance with Studor's installation instructions.


### APPLICATIONS

The innovative Maxi-Filtra is particularly suited for filtering bad odours resulting from the following applications:


- Septic tanks.
- Outside installations.
- Existing open vents.
- Newly installed open vents required by local regulations.
- Lifting stations.

### ALUMINIUM COVER (OPTIONAL)


The Aluminium Cover provides increased protection to the Maxi-Filtra when it is installed outside. The cover is placed over the upper half of the polystyrene cap provided and secured in place with adhesive tape. This provides increased protection from animals/birds and the environment, i.e. inclement weather and the sun's ultra-violet rays.




Aluminium cover




Insulating cap



Maxi-Filtra



Connector



Cartridge

### PIPE SIZES

Europe	AU/NZ	USA
DN 75-110	DN 80-100	3" - 4"

### DIMENSIONS

Dimension	Metric (mm)	Imperial (inches)
A	Ø 175	6 7/8"
B	1.5	1/6"
C	92	3 5/8"
D	155	6 1/8"
E	17	11/16"
F	84	3 5/16"
G	Ø 130	Ø 5 15/16"
H	131	5 3/16"
I	Ø 83	2 1/4"
J	Ø 89	Ø 3 1/2"
K	Ø 111	Ø 4 3/8"
L	50	2
M	Ø 75	Ø 2 15/16"
N	Ø 106	Ø 4 3/16"
O	Ø 70	Ø 2 3/4"
P	31	Ø 1 1/4"

Note: Dimensions for reference only

### PERFORMANCE PARAMETER

Temperature range	-20°C to +60°C (Europe/AU) -40°F to +150°F (USA)
-------------------	---

### MATERIALS

Component	Material
Aluminium cover	Aluminium
Insulating cap	Polystyrene
Maxi-Filtra body	ABS
Connector	Rubber
Cartridge	Activated carbon

### WARRANTY

The Studor products have a lifetime warranty - equivalent to that of the drainage system in which they are installed.



**STUDOR®**  
INVENTIVE TECHNOLOGY  
SINCE 1975

Technical Support and Design Assistance:

Tel: +44 845 601 3292 Fax: +44 845 601 3293

Email: support@studor.net

www.studor.net

STUDOR reserves the right to make changes to the product which may affect the accuracy of information contained in this document

0411-0004